
SUN ODYSSEY

Sun Odyssey 469







Certification conform with CE regulation.

SPECIFICATIONS


2 Harken electric winches (compatible with all genoas)

Furling mast aluminium mast with double spreaders


MAST AND RIGGING

Classic mast aluminium with double spreaders

2 Winch handles







SO 469

SO 509

Overall length		14,05 m	15,38 m
Hull length		13,65 m	14,98 m
Waterline length		12,54 m	13,92 m
Beam		4,49 m	4,69 m
Displacement light load with deep draft keel		10800 kg (provisoire)	13900 kg
Standard draft cast iron fin keel		2,24 m	2,28 m
Standard keel weight		3095 kg	4300 kg
Shoal draft cast iron fin keel		1,65 m	1,73 m
Shoal keel weight		3440 kg	4750 kg
CE category (* in process)	<i>(</i>	410 / BII / CI4 (*)	AI2 / BI4 / CI6
Fuel		240 L	240 L
Water		615 L	615 L
Fridge compartment		255 L	255 L
Holding tank		80L	80L
Architect / designer		Philippe Briand /	Philippe Briand /
		Jeanneau Design	Jeanneau Design
SAILS			
Standard sails horizontally-cut in high-quality dacron		■ 49,60 m²	■ 61,00 m ²
Standard headsail 106% horizontally-cut in high-quality dacron		■ 46,50 m²	■ 53,00 m²
Performance Headsail 140% in triradial cut mylar/taffeta laminate		□ 60,30 m²	□ 72,00 m²
Performance Headsail 106% in triradial cut mylar/taffeta laminate		□ 46,60 m²	□ 53,00 m²
Self-tacking jib in triradial cut mylar/taffeta laminate		□ 38,40 m²	□ 44,00 m²
Performance Mainsail in triradial cut mylar/taffeta laminate		□ 49,60 m²	□ 61,00 m ²
Inmast furling horizontally-cut in high-quality dacron		□ 38,00 m²	□ 49,00 m²
Code 0 in triradial cut mylar/aramid laminate		□ 84,40 m²	□ 97,00 m ²
S A I L H A N D L I N G			
Long Harken mainsail traveller with ball-bearing cars and control lines led aft to	to cockpit		-
Genoa tracks on coachroof with cars			
Genoa tracks on coachroof with ball-bearing cars adjustable from the cockpit			
Ballbearing tracks on sidedecks for large overlapping genoa			
Ballbearing track on coachroof for self tacking jib			
Harken winches and spinlock line stoppers			
Harken 46.2 Self-tailing port roof-mounted winch for halyards			-
Harken 46.2 Self-tailing starboard roof-mounted winch for halyards			
I Harken 46.2 Electric winch on the coachroof for halyards and control lines, I	2v	PREFERENCE	PREFERENCE
2 Harken self-tailing winches located near helm consoles for genoa and mainsh	eets	■ ST 50	■ ST 60
2 Harken ugraded self-tailing winches, included in option "rigging for large of	ovelapping genoa"	□ ST 60	□ ST 70
		- CT F0	- CT (0

□ ST 50

□ ST 60

	SO 469	SO 50
Aluminium boom with rigid vang	-	-
Single backstay	-	
Backstay with hydraulic adjuster		
Genoa furler with twin grove and furling line led to cockpit	-	
Below deck genoa furler with furling line led to cockpit	-	
Running rigging boom topping lift, main halyard, jib halyard, main sheet, jib sheets in polyester		-
Running rigging is low-stretch Dyneema		
Standing rigging is discontinuous wire 1x19		-
Standing rigging is Dyform discontinuous wire		
Tack point reinforcement at stem head for attachment of asymetrical spinnaker or code 0		
Running rigging for asymmetrical spinnaker / code 0 includes: 2 sheets, Ihalyard, I downhaul, turning blocks for mast base and sidedecks		
Running rigging for symmetrical spinnaker includes: 2 sheets, 2 guys, I halyard, tranck and inboard end car for the front of the mast, blocks for running rigging, spinnaker pole that stores on the mast		
Releasable forestay for staysail (option not compatible with self-tacking jib) Windex 15		
Lazy bag with integrated lazy jacks Halyard bags		
C O C K P I T		
Large cockpit table with storage compartments, icebox, space for instruments		
Folding teak cockpit table replaces GRP cockpit table with all the same functions	-	_
Wood battens on bench seats, fold-down platform and transom		
Teak battens on cockpit floor		_
Cockpit lockers 2 under bench seats, 2 large lockers under helm stations and 1 central locker designed to hold the optional generator		
Gas locker for 2 gas bottles, cut-off valve under stove		
2 Steering stations wheels with a leather wrap, space for flush mounted gps at each helm, stainless steel handrail		-
Composite steering wheels black, replaces standard wheels		
Emergency tiller fitting in cockpit floor		
Engine control throttle lever and engine panel located at starboard helm		-
360 docking with joystick mounted at cockpit table	□ POD 90	□POD
Large aft fold-down swim platform with telescopic ladder	•	-
Linear drive unit for aft platform motorises raising and lowering platform	PREFERENCE	PREFERE
Hinged companionway doors in plexiglas	-	
Sliding horizontal hatch in plexiglas		
Wide sprayhood in Sunbrella®		
Large 4 bow cockpit bimini with viewing ports above each helm that can be folded back and out of the way when not in use		
Cockpit cushions with closed-cell foam and covered in Sunbrella®		
DECK HARDWARE		
Open bow pulpit in stainless steel		
Stern pulpits in stainless steel with bracket for buoy		
Stemhead fitting in stainless steel with double anchor rollers	-	
Lifelines 2 levels of stainless steel wire, lifeline gates		
Toerail	•	
Mooring cleats x6 in aluminium		
Stailess steel cleats replacing standard aluminium cleats	PREMIERE	PREMIE
Handrails on coachroof in solid wood		-
Anchor locker Anchor windlass 12v with chainwheel	— 1000\A/ 10	- 1500\A/
Anchor Windiass 12V with chainwheel	■ 1000W - 10mm	■ 1500W -
Consend windless control was a data the with the consens		
Second windlass control mounted cockpit table with chain counter Took side deals		
Teak sidedecks		
Teak sidedecks Wooden rubrail located just below deck edge		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line		-
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle		-
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom		-
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed		-
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom	-	-
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports	- - - - - 8	-
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel TECHNICAL FEATURES AND OPTIONS CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 25kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel TECHNICAL FEATURES AND OPTIONS CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access via lockable deck hatch Access ladder in stainless steel TECHNICAL FEATURES AND OPTIONS CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull Injected deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION Hull : monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull Injected deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING LED navigation lights		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches Sall LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel TECHNICAL FEATURES AND OPTIONS CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull lipicated deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING LED navigation lights LED navigation lights LED and halogen interior lighting		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION Hull : monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull Injected deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING LED navigation lights		
Teak sidedeks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull Injected deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING LED navigation lights LED and halogen interior lighting LED and halogen interior lighting LED indirect lighting (not available for every version)		
Teak sidedecks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Opening hatches Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access via lockable deck hatch Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION Hull : monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull Injected deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING LED analygation lights LED and halogen interior lighting LED and halogen interior lighting letter than a soft blue light, 12V plug, 1cd display Main electric panel at navigation station backlit in a soft blue light, 12V plug, 1cd display		
Teak sidedeks Wooden rubrail located just below deck edge Mooring kit 4 braided dock lines 6 fenders Anchoring kit 20kg DELTA anchor with 32m of 10mm chain and 45m of line Anchoring kit 20kg DELTA anchor with 40m of 12mm chain and 50m of line Electric seawater washdown pump 12V in anchor locker with hose and nozzle Hydraulically operated gangway on transom Long lateral coachroof windows drape-formed Large, fixed hull ports Opening ports Opening ports Curtain set for windows ports and hatches insect screens for hatches SAIL LOCKER FORWARD Access via lockable deck hatch Access via lockable deck hatch Access ladder in stainless steel T E C H N I C A L F E A T U R E S A N D O P T I O N S CONSTRUCTION Hull: monolithic GRP hull hand-laid into a 2-part opening mould. ISO gelcoats. Barrier coat used to guard against osmosis 3rd Generation counter-moulded structure glued and laminated to hull for strength. High-load zones cut-out for access to the hull Injected deck via Prisma Process®. This process yields a very high-end part that is finished on both sides and reduces the weight by 30% with minimum impact on the environment LIGHTING LED navigation lights LED and halogen interior lighting LED and halogen interior lighting LED indirect lighting (not available for every version)		

SO 46	9 5	O 509

	30 407	
Additional house bank batteries 2 X 110 A/H	PREMIERE	PREMIERE
Engine alternator: 80A	•	
Battery switches: in the aft cabin		
2 x 40 amp battery chargers for 12V battery banks to ensure rapid recharging at the dock or when using the generator	PREMIERE	PREMIERE
2000W inverter		
Generator ONAN 6KW 220V 2400RPM its sound shield and located in a sound-shielded compartment in the transom, access via water-tight hatch		
Solar pannels on coachroof 2 x Solara 68W		
PLUMBING		
FRESH WATER		
Fresh water system with high-pressure 12v pump (1 9l/min) inline filter and accumulator tank		
2 Roto moulded water tanks 3851 tank under the forward berth and 2301 tank under aft cabin berth		
Tank manifold with selector valves		
Tank gauges located at the electrical panel		
40 L hot water heater connected to engine heat exchanger and 220v electrical system		
Hot and cold water shower at the transom		
Dock water inlet with pressure regulator. Allows the use of onboard systems without using water in the tanks when at the dock	PREFERENCE	PREFERENC
Dessalator water maker located under port side settee in saloon, operates on 12V and 220V for maximum efficiency, capacity 60 L per hour	-	
Raw and waste water		
Shower pumps with macerator function, activation of shower pumps via switch		
Manual marine toilets with large bowl		
Roto moulded holding tank 80 I located in aft port head		
BILGE DRAINAGE		
Electric bilge pump located in bilge area with activation via switch at electrical panel		
Electric bilge pump located in the forward sail locker, with activation via float switch, with separate hose from primary bilge pump		
Dual-action manual bilge pump located in the cockpit, with separate hose from primary bilge pump		
ENGINE AND STEERING		
Yanmar 4JH5-CE Sail Drive 4-cylinder Turbocharger - 54 HP / 39 KW - Engine alternator: 80A		-
Yanmar 4JH4-TCE Sail Drive 4-cylinder Turbocharger - 75 HP / 55 KW - Engine alternator: 80A	-	
Engine panel and throttle located near starboard helm		
on the stainless steel exhaust film, exhaust system roto moulded exhaust mixer with stainless steel exhaust fitting on hull		
GRP engine bed and liner, roto moulded exhaust mixer with stainless steel fitting on hull		
Compatible 360 docking	□ POD 90	□ POD 120
3-Blade fixed propeller		
3-Blade folding propeller		
Ventilation system extractor fan located in engine room		
Roto moulded fuel tank (240 I) located under aft cabin berth		
Access behind steps to engine compartment		
Extra diesel storage tank 240 L in lieu of one water tank	-	
Bow thruster 24V 11.5HP with separate 24V OPTIMA REDTOP battery bank		
NAVIGATION		
Electronic pack with 1 transducer for speed and depth in the hull, 1 wind sensor at masthead and 1 Raymarine i70 display on the cockpit table		
Raymarine E95 9" chart plotter display flush-mounted at starboard helm, with mapping (one per helm)		
Display on navigation data on TV in the saloon, ability to control the GPS from a tablette or smartphone		
4Kw raymarine digital radome and mast mount		
Raymarine signal radonic and mast mount Raymarine spx autopilot control computer with integrated gyro compass and hydraulic autopilot arm connected directly to steering quadrant		
VHF RAY55e with ais transponder at the chart table		

		SO 469			so	509	
	3C/2SE	3C/3SE	4C/4SE	3C/2SE	4C/2SE	4C/3SE	5C/3SE
COMFORT FEATURES AND OPTIONS							
DVD/CD/MP3 player with AUX input, 2 Bose® surround sound speakers in the saloon, I Bose® base unit and 2 waterproof exterior speakers located in the cockpit	PREMIERE						
Tv antenna for mast mounting							
26" LED TV mounted at nav station, pivots to be visible from settee and latches when underway, connected to dvd player and bose® 2.1 Surround-sound system							
LED TV in forward cabin 22" with a dvd/cd/mp3 player and 2 stereo speakers			-			-	-
Cruisair® air conditioning runs via shorepower or generator with 3 units	3200 BTU	3200 BTU	3200 BTU	4400 BTU	4400 BTU	4400 BTU	4400 BTU
Diesel forced air heating		-	-	-	-	-	-
Eberspacher® circulating water heating system 12,000W with outlets in all cabins and toilets	-						
INTERIOR FEATURES AND OPTIONS							
WOOD							
Alpi Fine Teak® interior with marine ply core, solid trim, anti-uv varnish							
Ceiling panels and hull liner wood panels with vinyl lining	-	-		-	-	-	
Laminate floorboards with light-coloured stripes and varnished edges							
Light oak laminate floorboards							
FORWARD CABIN							
Double berth with high-density foam mattress		-		-			
Mattress battens for owner's cabin berth			-			-	-
Extra wide cabin door for easy access (56cm)	-	-	-	-	-	-	-
Large hanging locker to starboard	-	-		-	-	-	
Additional hanging locker to port			-			-	-
An office/vanity area with leatherette desktop, mirror and storage area with light	-	-	-	-	-	-	-
Pneumatically-assisted opening storage cabinets under side deck			-				
Storage cabinets under side deck	-	-		-	-	-	-
LED reading lights and overhead led lighting							
Indirect led lighting (option) under upper storage cabinets			-			-	-
Full-length mirror			-			-	-
Handrail with leather wrap			-			-	-

■ Standard □ Option - Not available

		SO 46				509	
	3C/2SE	3C/3SE	4C/4SE	3C/2SE		4C/3SE	5C/3
Opening deck hatches, for light and ventilation	3	3	I	3	3	I	l
Large fixed hull port(s)	2	2	I	2	2	I	
2 Large storage drawers under berth + storage under berth with top access	-	-	-	•	•	-	
Storage for removable bulkheads under berth	-	-	-	-	-	-	
Night tables with leatherette lining	-	-	-			-	
Washrooms: solid surface countertop and moulded sink, storage cabinets, deck hatch to provide light and ventilation,							
LED overhead lighting and task lighting, standing shower separated by A plexiglas door (option), shower drain with							
switch, marine toilet with manual pump, clothes hook and towel bar, mirror							
Plexiglas shower dividers (owner's head)	PREMIERE	PREMIERE	-	PREMIERE	PREMIERE	-	
AFT CABIN							
Double berth with high-density foam mattress							
Hanging locker storage shelf along hull, night stand above engine compartment, storage shelf along engine compartment							
Led overhead lighting and reading light				-	•	-	
Indirect led lighting (option) along the bed				-	-	-	
I fixed hull port, I opening port into the cockpit for ventilation, I window in coachroof		•	-	-			
I Additional opening port into the cockpit (option)	PREMIERE	PREMIERE	PREMIERE	PREMIERE	PREMIERE	PREMIERE	PRE
I opening hatch		•					
Access to tanks and technical equipment in central corridor							
Washrooms: en-suite compartment with acces from cabin: en-suite compartments with day access from saloon, solid surface countertop with							
moulded sink, access to through-hulls and plumbing connections under sink, storage cabinets, opening port and fixed windows to provide light and							
ventilation, LED overhead lighting and task lighting, shower drain with switch, marine toilet with manual pump, clothes hook and towel bar, mirror							
Separate shower compartment with plexiglas door (option)		-	-			-	
LATERAL STARBOARD GUEST CABIN							
	_	_				_	
Two single, upper and lower bunks facing opposite directions			-	-			
Opening port and fixed window for light and ventilation	-	-	-	-	•	-	
NAVIGATION STATION							
Navigation station located to port behind the saloon	-		•				
Convertible navigation station located to starboard		-	-	-	-	-	
Chart table with leatherette worktop with opening compartment, space designed for laptop computer							
Large storage space under electrical panel for books and other navigation equipment							
Bookshelf under table with plexiglas dividers	-	-	-				
Chart reading light with red night-time vision mode	_						
SALOON							
Comfortable seating arrangement to port for 6 with view of sea though hull ports							
Hinged storage compartments under settee seating		•	•			•	
Large table with two removable, aluminium legs and central bottle storage		-	-				
Folding de luxe table in main saloon with bar and storage drawers in the fixed base (this table is not convertible into a berth)							
Central two-seats bench with storage	-			-	-		
2 Armchairs in the saloon with lock down mechanism when underway						-	
2 Lounge seats to starboard, backrest inserts in multiple colours, view of sea through hull ports		-	-			-	
Pullout bar cabinet with leatherette-lined table with bottle, glass storage and snack storage	-	-	-			-	
Upper storage cabinets with doors and fiddles							
Convertible berth in saloon with infill cushion for saloon table							
GALLEY				_			
Large, t-shaped galley to starboard of entryway allows 2 people to cook comfortably	-	-	-		-	-	
Large, L-shaped galley to starboard of entryway	-	-	-	-	-	-	
ong galley to starboard of entryway	-	-		-			
Solid counter tops				-			
Double stainless steel sinks with covers and chrome mixer tap							
Storage compartments with drawers and doors between the galley and the companionway	-	-	-	-			
arge utensil drawer forward with storage below and room for optional equipment	-	-	-		-	-	
Soft-close, fully-extending drawers							
Sliding waste bins with multiple compartments for selective sorting and recycling							
Upper storage cabinets with storage and space for optional microwave	-		-				
Phones storage capillets with storage and space for optional microwave							
175L fridge with top access, 12v compressor	-	-	-	-	-	-	
30L icebox with top access (optional freezer compressor)		•	•	•		•	
Opening port above stovetop for ventillation			•				
3 burner cooker and oven with grill function (replaces standard 2 burner cooker)	PREMIERE	PREMIERE	PREMIERE	PREMIERE	PREMIERE	PREMIERE	PREI
Microwave installed in galley							
Washer and dryer unit 220V located bottom of hanging locker, capacity 5kg			-		-	-	
Dishwashing machine 220V located in cabinet forward of galley (not compatible with additional fridge or wine cooler options)	-	-	-		-	-	
Wine cooler located in cabinet forward of galley							
(not compatible with additional fridge or dishwasher options)	_	_	_		_	_	
Additional fridge located in cabinet forward of galley (not compatible with wine cooler or dishwasher options)		-	-		_	-	
		_	-			-	_
H E A D R O O M							
Forward cabin	1,87 m			I,86 m			
Aft cabin(s)	1,97 m			I,97 m			
	1,97 m		I,98 m				
Companionway		1,94 m / 1,97 m		I,95 / I,98 m			
Companionway Saloon	1,	94 m / 1,97	m		1,95 /	1,98 m	



■ Standard \Box Option - Not available C = Cabins H = Head

